Work Orde								F	Page 1
Revision ID:	D3997-13			Accept				Setup Sta	
100111 1 (41110)	1/18/10	Start Qty: 10.00 Req'd Qty: 10.00		B1	Cust Item Customer:				
Approvals:	Process Pla	in: Pl	Date://-/-/8	Tooling: SPC (Y/N):		Pate:	 ·	Run Sta	op
Sequence ID/ Work Center II		Operation Description		Set Up/ Run Hours	Draw Number		lan Acce	ept Reject Qty	Reject Insp. Number Stamp
Draw Nbr D3997	Rev A	ision Nbr						··	
100 Purchasing Purchasing		Manufactu Possible St	re as per Dwg D3997 pplier:Studio Lettrage lease note required	0.00			/	pl co	(10)
110 Packaging Packaging		Receive & Inspect for D	amage & Mat'l Certs	0.00			/	10/07	/20 (w)

120

Quality Control

QC6-Inspect dimensions to drawing

0.00 2 510/01/21

Memo

D	art	Aer	ospa	ce	Ltd
---	-----	-----	------	----	-----

W/O:		WORK	ORDER CHANGES					E 6 1
DATE	STEP	PROCEDURE CHANGE	1	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
Part No):	PAR #: Fault Category:	NCR:	Yes	No DQ	A:	Date:	<u> </u>

Resolution: _____ Disposition: ____ QA: N/C Closed: ____ Date: ____

NCR:			WORK ORD	ER NON-CONFORMANC	E (NCR)			
		Description of NC	Corrective Action			Verification	Approval Chief Eng	
DATE	STEP	Section A	Initial Action Description Sign & Chief Eng Ch		Section C	Approval QC Inspector		
	!							
							20.	
		100			***			

NOTE: Date & initial all entries

Work Order ID 55408



Page 2

January 18, 2010 10:45:56 AM

Item 1D:

D3997-13

Accept

Setup Start

Stop

Revision ID:

Start Date:

Placard Item Name:

Required Date: 1/25/10

1/18/10

QC:

Start Qty: 10.00 Req'd Qty: 10.00

Operation

Description

Cust Item ID:

Customer:

Draw

Number

Reference:

Approvals:

Process Plan:

Date:

Date:

Tooling:

Date:

Start

SPC (Y/N):

Set Up/

Run Hours

Date:

Stop

Sequence ID/ **Work Center ID**

130

Packaging

Memo

0.00

0.00

Draw Rev.

Plan Code

Accept Reject Qty Qty

Run

Reject

Insp. Number Stamp

140

Packaging

QC21- Final Inspection - Work Order Release

Identify as per dwg & Stock Location 69

0.00

Quality Control

Memo

0.00

10/01/22/9 MF 10-1-21

Dart Ae	rospace	Ltd
---------	---------	-----

W/O:			WO	RK ORDER CHANG	ES		·			t + +
DATE STEP		PROCEDURE CHANGE				Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
Part No	:	PAR #:	Fault Categ	ory:	_ NCR	: Yes	No D Q	A:	_ Date: _	
	Res	solution:	Disposition	:	QA:	N/C CId	sed:		Date: _	
NCR:			WORK ORDE	R NON-CONFORM	ANCE	(NCR)			
5.475		Description of NC	Corrective Action		Section B		Verifi	cation	Approval	Approval
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng		Sign & Date		tion C	Chief Eng	QC Inspector
				1161						

NOTE: Date & initial all entries

. Picklist Print

January 18, 2010 10:46:00 AM

Work Order ID: 55408

Component Item ID/

Item Name

D3997-13P

D3997-13 Parent Item:

Parent Item Name: Placard

IPP rev A 10.01.12 new issue Prelim EC verified by:DD Comments:

Item ID

Purch

Purchased

Bin Primary Replacement Mfg/

Item Location

No

Location

Last

Seq ID

Route

Qty on Unit of Measure Hand Each

Qty To Pick 0.0000

10.0000

Start Date: 1/18/10

Start Qty: 10.00

Remaining

Qty

Issued

MF 10-1-21

Required Date: 1/25/10

Required Qty: 10.00

Date

Issued

Page 1


Status

Placard

Dart Ae	rospace Ltd							
W/O:			WORK ORDER	CHANGES				t , ,
DATE	STEP	PR	OCEDURE CHANGE	Ву	Date	Qty	Approval Chief Eng / Prod Mgr	Approval QC Inspector
Part No	:	PAR #:	Fault Category:	NCR : Ye	s No DQ	A :	Date: _	
	Resolutio	n:	Disposition:	QA: N/C	Closed:		Date: _	
NCR:			WORK ORDER NON-CON	FORMANCE (NO	R)			

NCR:	NCR: WORK ORDER NON-CONFORMANCE (NC				CE (NCR)			
		Description of NC Corrective Action Section B			Verification	Approval	Ammuoval	
DATE	STEP	Section A	Initial Chief Eng	Action Description Chief Eng	Sign & Date	Section C	Chief Eng	Approval QC Inspector
							i	
				10 to 14 to 10 to		***************************************		
					1			

NOTE: Date & initial all entries





210 MAIN W., HAWKESBURY, ONT. K6A 2H6

Tel.: 613 632-2001 Fax: 613 632-9491 www.studiolettrage.com INVOICE / FACTURE

No.:

13302

DATE:

01/20/2010

PAGE

1 of 1

Re: Quote No. 8181

VENDU À: SOLD TO:

Dart Aerospace Ltd

1270 Aberdeen Hawkesbury, Ontario

K6A 1K7

LIVRÉ À: SHIPPED TO:

Dart Aerospace Ltd

Hawkesbury, Ontario

ITEM ARTICLE	QTY UNIT QYÉ UNITÉ	DESCRIPTION	GST PST TPS TVP	UNIT PRICE PRIX UNITÉ	AMOUNT MONTANT
	22 10 10 10 10 10 10 10 10 10 10 10 10 10	set up for labels D3997 11P ! D3997 13P ? D3997 15P ? D3997 19P \$ D3997 21P 6 D3997 23P 1 D3997 25P \$ D3997 27P 9 D3997 33P !? D3997 35P !? D3997 37P !4 D3997 37P !4 D3997 3P !5 D3997 5P ? D399	E	275.00	275.00
Studio de Lettrage O 11156	GST: #869034678RP001			TOTAL	981.75



PRODUCT DATA BULLETIN

Product Data Bulletin: A5-0 Avery Graphics™ A5 Opaque 5-year INTERMEDIATE calendered vinyl film Dated: 10/3/02

Avery Graphics A5 Opaque intermediate films are flexible, high-gloss calendered vinyls designed for use on computer sign cutting equipment. This construction provides excellent cutting, weeding and transferring characteristics for signage applications.

Application information can be found in the Avery Graphics Application Guide.

For surface preparation, converting and printing, and application and removal instructions, please refer to the Avery Graphics Instructional Bulletin.

Construction:

- Face Film: 3.2 mils opaque medium gloss intermediate calendered vinyl film
- Adhesive: 1.0 mil clear acrylic permanent solvent pressure-sensitive adhesive
- Liner: 78# bleached white kraft

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification).

- Outdoor durability: 5 years when properly processed and applied (vertical exposure, unprinted film)**
- Application surface contours: Flat and simple curves
- Minimum surface and air application temperature: +50° F (10° C)
- Service Temperature Range: -40° F to +180° F (-40° C to 82° C) (Reasonable range of temperatures which would be expected under normal environmental time and temperature conditions)
- Typical Chemical Resistance: Resistant to most mild acids, alkalis and salt solutions. See instructional bulletin for recommendations on cleaning.
- Shelf Life: One year when stored at the following temperatures and humidity conditions: 68°-77° F (20° - 25° C) and 50±5% R. H.
- fypical Adhesion Values: 180° Peels

1 week 24 hrs Substrate 5.1 lbs/in 4.4 lbs/in Stainless Steel 5.3 lbs/in 4.7 lbs/in NOTE: Tested per ASTMO 1000. Always pre-test your specific substrate prior to actual application.

- Reflectivity: NA
- Typical Gloss*: 70 at 60°

Avery Graphics™ A5 Opaque page 1 of 2 AnswerLine: 800-443-9380 Signage.averygraphics.com

Product Bulletin 8522

3M

Release F, Effective January 2003

Black bar in margin indicates a change

Scotchcal [™] Opaque Imaging Media 8522

Description

This media is specially formulated to dry quickly after printing. Production of outdoor weatherable and long-term indoor durable graphics is now easier than ever. Its changeable adhesive allows easy removal for up to one year.

Advantages

- Optimized for use with selected Epson Stylus Proprinters and Epson Archival inks.
- Optimized for use with selected HP DesignJet Printers and HP DesignJet Ink System UV or HP83UV Color Ink System
- For making opaque, laminated graphics that are outdoor weatherable and long-term indoor durable
- Media:
 - For opaque (reflective) graphics
 - Changeable, easy to remove from warranted substrates up to 1 year later
 - Dries quickly after printing so the overlaminate can be applied almost immediately
 - Low slippage paper liner for superior tiling
- Overlaminates:
 - Provide additional UV (ultraviolet) and physical protection for making weatherable finished graphics
 - Available in luster and matte gloss
 - Adhesive allows for heat-assisted or cold-temperature lamination

Applications and Uses

3M[™] Scotchcal [™] Changeable Opaque Imaging Media 8522 is intended only for ink jet printing and for use with the listed Compatible Products and Equipment and the following applications. Any other application is NOT warranted by 3M or covered by the worldwide 3M [™] MCS [™] Warranty unless 3M gives its prior written approval for the application.

- First surface images (the image is on top of the film) for opaque posters and signs, including:
 - Graphics for vans, personal vehicles, trucks and buses
 - Novelty posters
 - Retail and point-of-purchase displays
 - Information graphics such as maps and directories
 - Entertainment promotions in museums, zoos, parks, theatres, sports venues
 - Education and presentation graphics

- Legal and courtroom exhibits
- For flat or simple curved surfaces, with or without rivers, used in vertical (± 10°) applications

Limitations of End Uses

The following uses and applications are specifically NOT warranted.

- Fleet applications in areas that use salt for winter road maintenance
- Application to non-warranted substrates, including wallhoard
- · Applications subjected to gasoline vapors or spills
- Application to corrugated or highly irregular surfaces or sharply raised areas
- Graphics applied to stainless steel, including stainless steel vehicles
- On flat surfaces with rivets, tenting of 4 to 10 mm around rivets may be expected; rivets may be cut around to eliminate tenting.

Note: Standard ink jet technology is water based. Waterbased chemistry is susceptible to the extremes of heat and humidity. This is a factor in most product constructions on the market. Read the Fabrication, Shelf Life and Storage sections in this bulletin. Staying in the middle of these ranges always provides optimum performance.

Compatible Products and Equipment

Thermal Ink Jet Printing Systems

- Epson Stylus Pro 9500, Stylus Pro 10000 printer
 - Epson Archival Inks
- Epson Stylus Pro 10600 printer
 - Epson Archival Inks
- HP DesignJet Printers 2000 and 3000 series
 - HP DesignJet Ink System UV (pigment-based ink)
- HP DesignJet Printers 5000 series
 - HP83UV Color Ink System

Overlaminates (required)

- 3M[™] Luster Overlaminate 8519 (semi-gloss)
- 3M[™] Matte Overlaminate 8520

Note: For the full product names of the 3M products listed on this page, please see page 1.

Warranted Substrates

Media 8522 is warranted for use on the following rigid substrates.

Some substrates may "out-gas", resulting in tiny bubbles throughout the surface of the graphic. For maximum performance, be sure the substrate you select is properly cleaned and prepared as recommended by the manufacturer. See Instruction Bulletin 5.1 for additional information.

- Alodine (anodized aluminum)
- Automotive panels (automotive painted steel)
- Fruehauf (painted aluminum)
- FRP (fiberglass reinforced plywood)
- Imron® (polyurethane-painted metal panel)
- Acrylic
- Sintra board

Test and Approve Non-warranted Substrates Before

Media 8522 is not warranted for any substrate other than those listed above. If you want to use it for other substrates. 3M recommends that you test and approve the media for both adhesion and removal characteristics.

Characteristics

Characteristic	Description
Media	7 mil, white, opaque graphic film
Liner	Low-slippage, lay tlat paper
Adhesive	Changeable, pressure sensitive
Thickness (media and adhesive)	7.5 to 8 mil (nominal)
Application substrates	See Warranted Substrates, above
Application surfaces	Flat or simple curved surfaces, with or without rivets, used in vertical (± 10°) applications (no corrugations)
Application temperature range	28° to 110°F (-2° to 43°C) (air and surface)
Roll sizes	36" x 45 feet (914 mm x 13.5 m) 54" x 45 feet (1372 mm x 13.5 m)

How to Become a 3M Ink Jet **Registered Fabricator**

Only 3M Thermal Ink Jet Registered Fabricators are eligible to offer 3M MCS warranted graphics. In order to become certified, a fabricator must complete the requirements as specified in the 3M Ink Jet Graphics Registered Fabricator Reference Manual located on the 3M website at www. scotchprint.com

Effective Performance Life

To obtain the warranty given below, the graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3. Also see the section, Removability.

Warranted Durability

Media 8522	Epson Pr	inters	HP Printers		
with Overlaminate 8519 or 8520	Outdoor	Indoor	Outdoor	Indoor	
Applied to Warranted Substrates	2 years	5 years	3 years	5 years	

Removability

Imaging media 8522 is removable from warranted substrates for I year without the aid of chemical strippers or accessories. Refer to Instruction Bulletin 4.23 for additional information.

Fabrication

Graphics must be made according to 3M's recommendations which are detailed in the Warranty and Limited Remedies on page 3.

See Instruction Bulletin 4.23 for detailed fabrication, printing and mounting information.

Graphic Construction Options

Opaque (Reflective) Graphics

Opaque graphics made with imaging media 8522 require an overlaminate and an opaque substrate.

Viewer/Light Source	
	Overlaminate 8519, 8520 Adhesive on bottom
	Imaging Media 8522 Image on top; adhesive on botton
	Image on top; adhesive on bottom
	Opeque Substrate

Note: For the full product names of the 3M products listed on this page, please see page 1.

Shelf Life and Storage

- 3M[™] Scotchcal[™] Changeable Opaque Imaging Media 8522 has a shelf life of one year.
- Storage conditions (new and partially used rolls). For optimum performance, use the middle of these ranges:
 - Original packaging, including plastic wrap
 - Relative humidity of 20% to 80%
 - Temperature of 33° to 104°F (0° to 40°C)
 - Away from direct sunlight
- Do not stack unprotected rolls or lay sharp or heavy objects on them.

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Material Safety Data Sheets (MSDS) for important health, safety and environmental information.

To obtain MSDS sheets for 3M products:

- By fax, call 1-800-364-0768 in the US and Canada or 1-650-556-8417 for all other locations.
- Electronically, visit us at http://www.3M.com/msds.
- By mail, or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

Warranty and Limited Remedies

3M ™ MCS ™ Warranty for Graphics Produced on HP DesignJet Printers and Epson Stylus Pro Printers

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose: We warrant graphics produced by a 3M Ink Jet Registered Fabricator made with imaging media 8522, printed on an approved HP thermal ink jet printer according to HP's recommendations or Epson Stylus Pro printer according to Epson's recommendations, overlaminated with 8519 or 8520, and applied to a Warranted Substrate according to 3M's recommendations. These

graphics are covered against failure caused by ultraviolet light, temperature extremes, pollution, and other elements.

If a graphic fails to perform in accordance with 3M product specifications within this time frame, 3M will replace the materials at no charge. These remedies are exclusive. In no case shall 3M be liable for any direct, indirect, or consequential damages, including any labor charges.

3M Related Literature

Listed below is related 3M technical literature that may be of interest. You may view and print these Bulletins from our Web site at www.scotchprint.com, or order them via our Faxon-Demand (FOD) system. Call one of these phone numbers to order the desired bulletins, and specify the FOD document number provided in the chart.

United States or Canada: 1-800-364-0768 International: 1-651-732-6506

International: 1-031-732-0000 Subject	Bulletin No.	FOD No.
Product Bulletins	-	
3M [™] Scotchcal [™] Overlaminate 8519 and 8520	8519/8520	4524
Instruction Bulletins		
Making thermal ink jet graphics	4.23	6523
Application, substrate selection, preparation and substrate-specific application techniques	5.1	7001
Warranties		7
Worldwide 3M [™] MCS [™] Warranty Packet (includes all Commercial Graphics MCS Warranties)		9503
Worldwide 3M™ MCS™ Warranty Overview-Folder		9504

3M. Scotchcal and MCS are trademarks of 3M.
Epson and Stylus Pro are trademarks of Epson.
HP and DesignJet are tradenames of Hewlett Packard.
Sintra is a trademark of Swiss Aluminum Ltd.
Imron is a registered trademark of DuPont in the United States

Bulletin Change Summary

The Epson Stylus Pro Printers 9500, 10000 10600, and Epson Archival Inks have been added to this bulletin. Additional changes resulting from this addition are marked with black bars in the margin.

ME

Commercial Graphics Division 3M Center. Building 220-6W-06 PO Box 33220 St. Paul, MN 55133-3220 USA General Info. 1-800-374-6772 Technical Info. 1-800-328-3908

3M Canada P.O. Box 5757 London, Ontario Canada N6A 4T1 1-800-265-1840 Fax 519-452-6245

Fax 1-651-736-4233 Fax-on-Demand 1-800-364-0768 US/Canada or 1-651-732-6506 International Fax-on-Demand document: 4506 www.scotchprint.com 3M México, S.A. de C.V.

Av. Santa Fe No. 55 Col. Santa Fe, Del. Alvaro Obregón México, D.F. 01210 52-55-52-70-04-00 Fax 52-55-52-70-22-77 3M Puerto Rico, Inc. Puerto Rico Industrial Park P.O. Box 100 Carolina, PR (00986-0100 787-620-3000 Fax 787-750-3035

©3M 2003. All rights reserved.

Product Bulletin 8522 – 3